

1199 PANIGALE

Specifications



DUCATI 1199 Panigale S Tricolore

Chassis

Frame	Monocoque aluminum
Front suspension	Öhlins NIX30 43mm with TiN, fully adjustable usd fork. Electronic compression and rebound damping adjustment
Front wheel	3-spoke forged light alloy 3.50" x 17"
Rear suspension	Fully adjustable Ohlins TTX36 unit. Electronic compression and rebound damping adjustment. Adjustable linkage: Progressive/flat. Aluminum single-sided swingarm.
Rear wheel	3 spoke forged light alloy 6.00" x 17"
Front brake	2 x 330mm semi-floating discs, radially mounted Brembo Monobloc M50 4-piston callipers
Rear brake	245mm disc, 2-piston calliper
Fuel tank capacity	17l (4.5 gallon US)
Dry weight	166.5kg (367lb)
*Wet weight	190.5kg (420lb)

Engine

Type	Superquadro: L-twin cylinder, 4 valve per cylinder, Desmodromic, liquid cooled
Bore x Stroke	112 x 60.8mm
Power	195hp (143kw) @ 10,750rpm
Torque	98.1lb-ft (132Nm) @ 9,000rpm
Exhaust	2-1-2 system with catalytic converter and 2 lambda probes. Twin stainless steel mufflers with aluminum outer sleeves

Transmission

Clutch	Slipper and self-servo wet multiplate clutch with hydraulic control
---------------	---